

# PowerHeart T

## 10~60kVA 3 Phases Rack UPS

### Power range

10 ~60 kVA

### Operation

3P/3P,3P/1P,1P/1P,Online double conversion

### Designed to **CARE**

Small & Medium Data Center, High Density Smart Solutions, Light Industrial Applications, Smart Industry, Medium and Large Offices, Corporate Buildings.

### Characteristics

- Mounted in 19 inch rack, or install as tower UPS.
- 7 inch touch LCD with IoT functions.
- Flexible configuration as 3/3,3/1,1/1.
- High power density, small volume, 30KW in 3U
- High reliability and environment adaptability.



Model	PHTT010LR	PHTT015LR	PHTT020LR	PHTT030LR	PHTT040LR	PHTT060LR
Rate Power	10kVA	15kVA	20kVA	30kVA	40kVA	60kVA
Main input	Input					
	Rate Voltage					
	Rate Freq.					
	Input PF					
	Current distortion					
	Voltage range					
	Freq. range					
Battery	Rate voltage					
	Charging capacity					
	Charging accuracy					
Bypass	Rate voltage					
	Voltage range					
	Frequency range					
Inverter	Rate voltage					
	Rate Freq.					
	Output PF					
	Voltage accuracy					
	Load response					
	Recovery time					
	Output THDu					
	Overload					
	Frequency accuracy					
	Synchronize window					
	Slew rate					
	Crest factor					
	Phase Accuracy					
	System	Efficiency				
Display						
Certification- Safety						
Certification- EMS						
IP degree						
Configuration						
Option						
Environment						
Dimension (W*D*H) mm	440*774*130 (3U)			440*788*174 (4U)	440*780*308 (7U)	
Weight(kg)	27	28	29	38	60	